

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.09.2011

Revision: 1

Revision: 27.09.2011

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** 390-RX-HT
- **Article number(s):** bz036
- **Relevant identified uses of the substance or mixture and uses advised against:** no data available
- **Application of the substance / the mixture:** Flux
- **Details of the supplier of the safety data sheet**
- **Manufacturer / Supplier:**
Balver Zinn
Josef Jost GmbH & Co.KG
Blintroper Weg 11
D-58802 Balve · Germany
Phone: +49 2375 915 – 0
Fax: +49 2375 915 – 114
E-Mail: Info@BalverZinn.com
- **Manufacturer:**
Cobar Europe BV
Aluminiumstraat 2
NL-4823 AL Breda · Netherlands
Phone: +31 76 5445566
Fax: +31 76 5445577
E-Mail: Info@Cobar.com
- **E-mail address of the competent person responsible for the Safety Data Sheet:** kontakt@trabaserio.eu
- **Informing department:** Technical Support of the Supplier
- **Emergency telephone number:** Giftnotruf Berlin +49 30 / 30686 790 - Helpdesk in German and English

2 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Xi; Irritant

R36: Irritating to eyes.



F; Highly flammable

R11: Highly flammable.

R67: Vapours may cause drowsiness and dizziness.

- **Information concerning particular hazards for human and environment:**
Has a narcotizing effect.

(Contd. on page 2)

-GB-

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.09.2011

Revision: 1

Revision: 27.09.2011

Trade name: 390-RX-HT

(Contd. of page 1)

Vapours of the product are heavier than air and may accumulate on the ground, in mines, drains or cellars with higher concentration.

In the gas volume of sealed packages vapours of flammable solvents, especially at action of heat, may accumulate. Keep away fire and ignition sources.

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· **Label elements**

· **Labelling according to EU guidelines:**

· **Code letter and hazard designation of product:**



Xi Irritant
F Highly flammable

· **Risk phrases:**

11 Highly flammable.

36 Irritating to eyes.

67 Vapours may cause drowsiness and dizziness.

· **Safety phrases:**

7 Keep container tightly closed.

16 Keep away from sources of ignition - No smoking.

24/25 Avoid contact with skin and eyes.

26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture consisting of the following components.

· **Dangerous components:**

CAS: 124-04-9 EINECS: 204-673-3 Index number: 607-144-00-9	Adipic acid Xi R36 Eye Irrit. 2, H319	≤2.5%
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0	Propan-2-ol Xi R36; F R11 R67 Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	75 - 100%
CAS: 25265-77-4 EINECS: 246-771-9	2,2,4-Trimethyl-1,3-pentanediol monoisobutyrate R52	≤2.5%
CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5	Benzyl alcohol Xn R20/22 Acute Tox. 4, H302; Acute Tox. 4, H332	≤0.1%

· **Additional information** For the wording of the listed risk phrases refer to section 16.

· **Ingredients according to Regulation (EC) No 648/2004:**

BENZYL ALCOHOL

GB

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.09.2011

Revision: 1

Revision: 27.09.2011

Trade name: 390-RX-HT

(Contd. of page 2)

4 First aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing contaminated by the product.
- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness bring patient into stable side position for transport.
- **After skin contact:**
Rinse with plenty of water.
After prolonged skin contact defatting of skin possible, use skin protecting agent after prolonged skin contact. If skin irritation continues, consult a doctor.
- **After eye contact:**
Rinse opened eye for several minutes under running water.
Use eye protection.
Call a doctor immediately.
- **After swallowing:**
Rinse out mouth and then drink plenty of water.
Do not induce vomiting - Danger of chemical pneumonia.
Seek medical treatment.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
Sickness
Headache
Dazed
Dizziness
Unconsciousness
- **Indication of any immediate medical attention and special treatment needed**
Subsequent observation for pneumonia and pulmonary oedema.

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents**
Carbon dioxide (CO₂), extinguishing powder or water spray/fog. Fight larger fires with water spray/fog or alcohol-resistant foam.
- **For safety reasons unsuitable extinguishing agents** Water with a full water jet.
- **Special hazards arising from the substance or mixture:**
Danger of bursting
Can be released in case of fire:
Flammable gases/vapours
Irritant gases/vapours
Carbon monoxide (CO) and Carbon dioxide (CO₂)
Under certain fire conditions, traces of other toxic gases cannot be excluded.
- **Advice for firefighters**
- **Protective equipment:**



Wear self-contained breathing apparatus.

- **Additional information:**
Cool endangered containers with water spray jet.
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.
If without risk possible, move drums with material away from dangerous area.

GB

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.09.2011

Revision: 1

Revision: 27.09.2011

Trade name: 390-RX-HT

(Contd. of page 3)

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation.

Use breathing protection against the effects of fumes/dust/aerosol.

Avoid skin and eye contact.

Remove all ignition sources.

Wear protective clothing and keep away unprotected persons.

- **Environmental precautions:**

Damp down gases/fumes/haze with water spray jet.

Do not allow to enter drainage system, surface or ground water.

Inform respective authorities in case product reaches water or sewage system.

Do not allow to enter the ground/soil.

If material reaches soil inform authorities responsible for such cases.

- **Methods and material for containment and cleaning up:**

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Send for recovery or disposal in suitable containers.

Dispose of the material collected according to regulations.

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

7 Handling and storage

- **Handling**

- **Precautions for safe handling**

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Do not inhale vapours/aerosols.

Make sure that all applicable workplace limits are observed.

Avoid skin and eye contact.

Open and handle container with care.

Avoid splashes or spray in enclosed areas.

Keep away from heat and direct sunlight.

- **Information about protection against explosions and fires:**

Protect against electrostatic charges.



Keep ignition sources away - Do not smoke.

Fumes can combine with air to form an explosive mixture.

Flammable mixtures may be formed in empty containers.

Use explosion-proof apparatus / fittings and spark-proof tools.

Have fire extinguishing equipment ready in case of nearby fire.

Keep breathing equipment ready.

Handle only outside or in explosion protected rooms.

- **Conditions for safe storage, including any incompatibilities**

- **Storage**

- **Requirements to be met by storerooms and containers:**

Observe all local and national regulations for storage of water polluting products.

- **Information about storage in one common storage facility:** Store away from oxidizing agents.

- **Further information about storage conditions:**

Store container in a well ventilated position.

Keep container tightly sealed.

Store in a cool place. Heat will increase pressure and may lead to the container exploding.

Store only outside or in explosion proof rooms.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.09.2011

Revision: 1

Revision: 27.09.2011

Trade name: 390-RX-HT

(Contd. of page 4)

- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Control parameters**

- **Components with critical values that require monitoring at the workplace:**

67-63-0 Propan-2-ol

WEL (Great Britain)	Short-term value: 1250 mg/m ³ , 500 ppm
	Long-term value: 999 mg/m ³ , 400 ppm

- **DNELs** no data available
- **PNECs** no data available
- **Additional information:** The lists that were valid during the compilation were used as basis.

- **Exposure controls**

- **Personal protective equipment**

- **General protective and hygienic measures**

Keep away from foodstuffs, beverages and food.

Instantly remove any contaminated garments.

Do not carry cleaning cloths impregnated with the product in trouser pockets.

Do not eat, drink or smoke while working.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Be sure to clean skin thoroughly after work and before breaks.

Apply solvent resistant clothing before beginning work.

- **Breathing equipment:**

Use breathing protection in case of insufficient ventilation.

If all workplace limits are observed and good ventilation is ensured, no special precaution necessary.

- **Recommended filter device for short term use:** Filter A

- **Protection of hands:**



Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

Check the permeability prior to each renewed use of the glove.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

To avoid skin problems reduce the wearing of gloves to the required minimum.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Protective gloves should be replaced at first signs of wear.

- **Eye protection:**



Tightly sealed safety glasses

- **Body protection:**

Solvent resistant protective clothing

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.09.2011

Revision: 1

Revision: 27.09.2011

Trade name: 390-RX-HT

(Contd. of page 5)

Antistatic protective clothing
Protective clothing should be selected specifically for the working place.

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: liquid
Colour: colourless
clear

· **Smell:** like alcohol
· **Odour threshold:** not determined

· **pH-value:** not determined

· Change in condition

Melting point/Melting range: not applicable
Boiling point/Boiling range: ~82°C (IPA)

· **Flash point:** 13°C

· **Inflammability (solid, gaseous)** Highly flammable.

· **Ignition temperature:** ~425°C

· **Decomposition temperature:** no data available

· **Self-inflammability:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures is possible.

· Critical values for explosion:

Lower: ~2 Vol % (IPA)
Upper: ~12 Vol % (IPA)

· **Oxidizing properties** not classified as oxidising

· **Vapour pressure at 20°C:** ~48 mbar

· **Density at 20°C** 0.813 g/cm³

· **Settled apparent density** not applicable
· **Vapour density (AIR = 1)** not determined
· **Evaporation rate** not determined

· Solubility in / Miscibility with

Water: soluble
· **Organic solvents:** Miscible with many organic solvents

· **Segregation coefficient (n-octanol/water):** no data available

· Viscosity:

dynamic: Not determined.
kinematic: not determined

VOC (EU) 75 - 100%

VOCV (CH) 75 - 100%

· **Other information** see technical data sheet

10 Stability and reactivity

· **Reactivity**
· **Chemical stability** Stable

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.09.2011

Revision: 1

Revision: 27.09.2011

Trade name: 390-RX-HT

(Contd. of page 6)

- **Thermal decomposition / conditions to be avoided:** Avoid impact, friction, heat, sparks, electrostatic charges.
- **Possibility of hazardous reactions**
 Danger of bursting
 Develops readily flammable gases / fumes
 Used empty containers may contain product gases which form explosive mixtures with air.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Strong oxidizing agents
- **Hazardous decomposition products:**
 Irritant gases/vapours
 Carbon monoxide (CO) and Carbon dioxide (CO₂)

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

67-63-0 Propan-2-ol

Oral	LD50	3600 mg/kg (mouse)
		4570 - 5045 mg/kg (rat)
		6410 mg/kg (rabbit)
	LDLo	3570 mg/kg (human)
Dermal	LD50	12800 - 13400 mg/kg (rabbit)
Inhalative	LC50/4 h	30 - 46.5 mg/l (rat)

124-04-9 Adipic acid

Oral	LD50	~5700 mg/kg (rat)
Dermal	LD50	> 7940 mg/kg (rabbit)
Inhalative	LC50/4 h	> 7.7 mg/l (rat) (BASF-Test)

25265-77-4 2,2,4-Trimethyl-1,3-pentanediol monoisobutyrate

Oral	LD50	6517 mg/kg (rat)
Dermal	LD50	> 15200 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** Long or repeated contact can defat skin and may cause dermatitis.
- **on the eye:** Causes serious eye irritation.
- **Sensitization:** No sensitizing effect known.
- **Additional toxicological information:**
 The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:
 Irritant
 Inhalation of concentrated vapours may lead to anaesthesia-like conditions and headache, dizziness, etc.

12 Ecological information

- **Toxicity**

· **Aquatic toxicity:**

67-63-0 Propan-2-ol

EC50/24 h	> 1000 mg/l (water flea (daphnia magna))
EC50/48 h	13299 mg/l (water flea (daphnia magna))
IC50/72 h	> 1000 mg/l (algae (scenedesmus subspicatus))
LC50/48 h	8970 mg/l (leuciscus idus)
LC50/96 h	9640 mg/l (fathead minnow (pimephales promelas))

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.09.2011

Revision: 1

Revision: 27.09.2011

Trade name: 390-RX-HT

(Contd. of page 7)

124-04-9 Adipic acid

EC50/17 h	91.9 mg/l (<i>pseudomonas putida</i>)
EC50/3 h	7.911 mg/l (<i>pseudomonas putida</i>)
EC50/48 h	86.5 mg/l (<i>water flea (daphnia magna)</i>)
EC50/72 h	31.3 mg/l (<i>algae (scenedesmus subspicatus)</i>)
LC50/48 h	100 - 511 mg/l (<i>leuciscus idus</i>)
LC50/96 h	88 - 97 mg/l (<i>fathead minnow (pimephales promelas)</i>)

25265-77-4 2,2,4-Trimethyl-1,3-pentanediol monoisobutyrate

EC50/48 h	> 19 mg/l (<i>water flea (daphnia magna)</i>)
EC50/72 h	13 mg/l (<i>algae</i>)
LC50/96 h	33 mg/l (<i>fish</i>)

- **Persistence and degradability** biodegradable
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **Chemical Oxygen Demand (COD-value):** not determined
- **BOD5-value:** not determined
- **According to recipe contains the following heavy metals and compounds according to EC guideline NO. 76/464 EC:**
The product does not contain heavy metals.
- **General notes:** Water hazard class 1 (Self-assessment): slightly hazardous for water
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**



Disposal must be made according to official regulations.

- **Waste disposal key number:** According to local/national regulations.

- **European waste catalogue:**

07 07 04*	other organic solvents, washing liquids and mother liquors
-----------	--

- **Uncleaned packagings:**
- **Recommendation:**
Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning. Packagings that cannot be cleaned are to be disposed of in the same manner as the product.
- **Recommended cleaning agent:** Water

14 Transport information

- **UN-Number**
- **ADR, IMDG, IATA** UN1219
- **ADN** UN1993

(Contd. on page 9)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.09.2011

Revision: 1

Revision: 27.09.2011

Trade name: 390-RX-HT

(Contd. of page 8)

· **UN proper shipping name**
· **ADR**
· **IMDG, IATA**

UN 1219 ISOPROPANOL, MIXTURE
ISOPROPANOL, MIXTURE

· **Transport hazard class(es)**
· **ADR**



· **Class**
· **Label**

3 (F1) Flammable liquids.
3

· **IMDG, IATA**



· **Class**
· **Label**

3 Flammable liquids.
3

· **Packing group**
· **ADR, IMDG, IATA**

II

· **Environmental hazards:**
· **Marine pollutant:**

Not applicable.
NO

· **Special precautions for user:**
· **Kemler Number:**
· **EMS Number:**

Warning: Flammable liquids.
33
F-E,S-D

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:**

not determined

· **Additional Transport information:**

Transport by post may be prohibited or restricted.

· **ADR**
· **Excepted quantities (EQ):**
· **Limited quantities (LQ):**
· **Transport category:**
· **Tunnel restriction code:**

E2
1L
2
D/E

· **UN "Model Regulation":**

UN1219, ISOPROPANOL, MIXTURE, 3, II

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Designation according to EC guidelines:
- Code letter and hazard designation of product:



Xi Irritant
F Highly flammable

- **Risk phrases:**
11 Highly flammable.
36 Irritating to eyes.

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.09.2011

Revision: 1

Revision: 27.09.2011

Trade name: 390-RX-HT

(Contd. of page 9)

67 Vapours may cause drowsiness and dizziness.

· **Safety phrases:**

- 7 Keep container tightly closed.
- 16 Keep away from sources of ignition - No smoking.
- 24/25 Avoid contact with skin and eyes.
- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

· **National regulations**

· **Information about limitation of use:** Employment restrictions concerning young persons must be observed.

· **Decree to be applied in case of technical fault:**

Quantity limits according to „EC Seveso Directive“ should be observed.

· **Water hazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water

· **Other regulations, limitations and prohibitive regulations**

Observe restrictions on the marketing and use according to Annex XVII of Regulation (EC) No 1907/2006.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases:**

- H225 Highly flammable liquid and vapour.
- H302 Harmful if swallowed.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- R11 Highly flammable.
- R20/22 Harmful by inhalation and if swallowed.
- R36 Irritating to eyes.
- R52 Harmful to aquatic organisms.
- R67 Vapours may cause drowsiness and dizziness.

· **Department issuing MSDS:**

TRABASERIO S.L.
 C./Isabel II, N° 67, Pl. Baja A
 E-07100 Sóller / Spain
 Tel. & Fax: +34 971 63 34 64 · E-Mail: kontakt@trabaserio.eu

· **Date of first issue MSDS:** 27.09.2011

· **Abbreviations and acronyms:**

GGVSEB (Gefahrgutverordnung Straße, Eisenbahn und Binnenschifffahrt): Ordinance on the national and international carriage of dangerous goods by road, rail, and inland waterways
 ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 ICAO: International Civil Aviation Organization
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 CLP: Regulation on Classification, Labelling and Packaging of Substances and Mixtures
 DNEL: Derived No-Effect Level (REACH)
 PNEC: Predicted No-Effect Concentration (REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent