Zn99.995-Optiloop®

Date 2025.09.01 Language English **SDS** 950051



SUMMARY

Optiloop® is characterised by particularly efficient and uniform dissolution and is excellently suited for use with titanium baskets Soluble zinc anodes made of particularly pure SHG Special High Grade Zinc according to EN 1179 (Z1). When using titanium baskets, the Optiloop® is outstandingly suitable.

ALLOY	Zn99.995-Optiloop®	
PROCESS		
corrosion protection		9
Wear Protection		1
INDUSTRY APPLICATION		
Soluble anode		9
Insoluble anode		1

PROCESS CAPABILITY		
Flame spraying	1	
Arc Spraying	1	
Plain Bearing Process	1	
Capacitor contacting	1	
Electroplating	9	
Dissolution Behaviour	9	
Cast / Cast-in suspension		
Soldered suspension (copper)	1	

Legend		
Especially made for this purpose	9 - 10	
Generally qualified for this purpose		
Generally usable, but not the best choice		
Generally not usable for this purpose		
Wrong choice	1 - 2	

PROPERTIES				
Manufacturing standard	EN 1179: 2003 (Z1)			
Alloy Code	Optiloop®			
Alloy composition	Zn99.995			

COMPOSITION		
Zinc	[Zn]	99.995
Lead	[Pb]	max. 0.003
Cadmium	[Cd]	max. 0.005
Iron	[Fe]	max. 0.002
Tin	[Sn]	max. 0.001
Copper	[Cu]	max. 0.001
Aluminum	[AI]	max. 0.001

DELIVERY FORM		
Optiloop®	ØxH [mm]	Ø 41-50 x 25

Check material compatibility with every process change!

Read AN before use.

Read MSDS before use.

Disclaimer:
This information is intended as advice to the best of our knowledge. The provided data is based on our own measurements, they do not provide any guaranteed properties nor are these delivery specifications. Due to the versatility of materials, applications and taking in consideration the industrial property rights of third parties, Balver Zinn Josef Jost GmbH & Co. KG cannot take any liability.