## **Product Data Sheet**

## BALVER ZINN®

**REGI-GOLD** 

Pav. 24 6

 Date
 2024.06.07

 Language
 English

 SDS
 950333





## Summary

REGI-GOLD is a ROL0 classified, alcohol-based flux for high reliability applications. It is based on natural rosins and has high SIR values.

Flux code	REGI-GOLD	
PROCESS		
No-Clean process		9
Post-solder cleaning		8

INDUSTRY APPLICATION		
Standard electronics		
Industrial electronics		
Hi-Rel electronics (automotive)		

PROCESS CAPABILITY		
Foam fluxing	8	
Spray fluxing	9	
Short preheat	8	
Short contact time	9	
Pb-free process Air	9	
Pb-free process N2 wave	9	
Pb-free process N2 tunnel	9	
Skipped joints	9	
Solderballing	9	
Bridging	9	
Promotes wicking	8	
PTH filling	9	
Cosmetic cleanliness		
Cosmetic cleanliness N2	9	
Shiny joint appearance		
Pin testability		
Conformal coating (see AN)		

Legend		
Especially made for this purpose		
Generally qualified for this purpose		
Generally usable, but not the best choice		
Generally not usable for this purpose		
Wrong choice		

CLASSIFICATION		
DIN EN ISO 9454-1: 2016	1222	
IPC-J-STD-004-A: 2004	ROL0	

PROPERTIES			
Density	@20°C [kg/dm³]	0.8	
Solid content	[% w/w]	4.4	
Acid number	[mg KOH/g]	25.5	
Water content	[% w/w]	0	
VOC content	[% w/w]	Remainder	
Filmformer(s)		Rosin	
Color		Colorless	
Odor		Alcoholic	
Flashpoint COC	[°C]	13	
Thinners		425-00	

TEST REPORTS			
Certificate of Compliance		None	
Application Note			EN/DE
Copper Mirror	IPC-TM-650 2.3.32		Pass
Halides	IPC-TM-650 2.3.33	[Silver Chromate]	Pass
Halide	IPC-TM-650 2.3.35.1	[Fluoride by Spot]	Pass
Copper Corrosion	IPC-TM-650 2.6.15		Pass
SIR	IPC-TM-650 2.6.3.3		Pass
ECM	IPC-TM-650 2.6.14.1		in Progress

PACKAGING AND STORAGE		
Packaging can	(HDPE) [liter]	10
Packaging Drum	(HDPE) [liter]	200
Shelf-life in months	20-25 °C	6

Check material compatibility with every process change! Industrial chemical product.

Read SDS before use.

## Disclaimer

This information is intended as advice to the best of our knowledge. The provided data is based on our own measurements, they do not provide any guaranteed properties nor are these delivery specifications. Due to the versatility of materials, applications and taking in consideration the industrial property rights of third parties, Balver Zinn Josef Jost GmbH & Co. KG cannot take any liability.