Product Data Sheet

BALVER ZINN®

REGI-GREEN

Date 2024.07.12

Language English SDS 950421





Summary

REGI-GREEN is a partially water based ORL0 classified flux for wave soldering applications. It is based on organic acids and leaves hardly any visible residues. The REGI-GREEN also eliminates bridging.

Flux code	REGI-GREEN	
PROCESS		
No-Clean process		9
Post-solder cleaning		8

INDUSTRY APPLICATION		
Standard electronics	9	
Industrial electronics		
Hi-Rel electronics (automotive)		

PROCESS CAPABILITY		
Foam fluxing	8	
Spray fluxing	9	
Short preheat	8	
Short contact time	9	
Pb-free process Air	9	
Pb-free process N2 wave	9	
Pb-free process N2 tunnel	9	
Skipped joints	9	
Solderballing	9	
Bridging	9	
Promotes wicking	8	
PTH filling	9	
Cosmetic cleanliness	8	
Cosmetic cleanliness N2	9	
Shiny joint appearance	9	
Pin testability	8	
Conformal coating (see AN)		

Legend		
Especially made for this purpose	9 - 10	
Generally qualified for this purpose		
Generally usable, but not the best choice		
Generally not usable for this purpose		
Wrong choice	1 - 2	

CLASSIFICATION		
DIN EN ISO 9454-1: 2016	2122	
IPC-J-STD-004-A: 2004	ROL0	

PROPERTIES			
Density		@20°C [kg/dm³]	0.9
Solid content		[% w/w]	3.5
Acid number		[mg KOH/g]	35
Water content		[% w/w]	30
VOC content		[% w/w]	Remainder
Filmformer(s)			Organic
Color			Colorless
Odor			Alcoholic
Flashpoint COC		[°C]	13
Thinners			425-00

TEST REPORTS			
Certificate of Compliance			None
Application Note			EN/DE
Copper Mirror	IPC-TM-650 2.3.32		Pass
Halides	IPC-TM-650 2.3.33	[Silver Chromate]	Pass
Halide	IPC-TM-650 2.3.35.1	[Fluoride by Spot]	Pass
Copper Corrosion	IPC-TM-650 2.6.15		Pass
SIR	IPC-TM-650 2.6.3.3		Pending
ECM	IPC-TM-650 2.6.14.1		Pending

PACKAGING AND STORAGE		
Packaging can	(HDPE) [liter]	10
Packaging Drum	(HDPE) [liter]	200
Shelf-life in months	20-25 °C	18

Check material compatibility with every process change! Industrial chemical product.

Read SDS before use.

Disclaimer

This information is intended as advice to the best of our knowledge. The provided data is based on our own measurements, they do not provide any guaranteed properties nor are these delivery specifications. Due to the versatility of materials, applications and taking in consideration the industrial property rights of third parties, Balver Zinn Josef Jost GmbH & Co. KG cannot take any liability.