Product data sheet

BALVER ZINN®

BALVER BRAID

Rev: 25.11

Revised 2026.04.02
Release 25.11
Language English
SDS 950815

BALVERZINN.COM

SUMMARY

Copper mesh with flux, for desoldering / solder removal

PRODUCT	BALVER BRAID
PROCESS	
Manual Application	9
Lead-free	9
Lead-containing	9

INDUSTRY APPLICATION	
Consumer Electronics	9
Standard Industrial Electronics	9
Hi-Rel Electronics (automotive)	7

PROCESS CAPABILITY	
Soldering Iron Soldering	9
Hot Air Soldering	9
Desonldering Lead-free	8
Desonldering Lead-containing	9
Solder Removal Lead-free	8
Solder Removal Lead-containing	9

Legend	
Especially made for this purpose	9 - 10
Generally qualified for this purpose	7 - 8
Generally usable, but not the best choice	5 - 6
Generally not usable for this purpose	3 - 4
Wrong choice	1 - 2

CLASSIFICATION	
IPC-J-STD-004	REL0
Composition	Cu
Flux type	No-Clean
Color	Metallic
Color	Odorless

SHAPE AND DIMENSIONS*
Width 1,4 mm
Width 1,9 mm
Width 2,5 mm

PACKAGING AND STORAGE	
ESD-Safe Reel	1,5 m
Packaging Unit	25

Minimum shelf-life month's		
Dry at Ambient Temperature		24

Check material compatibility with every process change!

Industrial chemical product.

This information is intended as advice to the best of our knowledge. The provided data is based on our own measurements, they do not provide any guaranteed properties nor are these delivery specifications. Due to the versatility of materials, applications and taking in consideration the industrial property rights of third parties, Balver ZInn GmbH cannot take any liability.