



JEAN-151-SnPb36Ag2-T4

Rev: 21.7

Revised	2026.04.02
Release	21.7
Language	English
SDS	950711



SUMMARY

SnPb - Halide-free - No-Clean solder paste - Fine Pitch

PASTE	JEAN-151-SnPb36Ag2-T4	
PROCESS		
No-Clean process	9	
Post-solder cleaning	9	

INDUSTRY APPLICATION		
Standard electronics	8	
Industrial electronics	9	
Hi-Rel electronics (automotive)	9	

PROCESS CAPABILITY		
Squeegee	9	
ProFlow	TBD	
Pb-free Profile Air, short	1	
Pb-free Profile Air, long	1	
Pb-free process N2	1	
Vapor phase process	8	
Shiny joint appearance	9	
Cosmetic cleanliness	8	
ICCT compatible	N/A	
Conformal coating	N/A	

Legend		
<i>Especially made for this purpose</i>	9 - 10	
<i>Generally qualified for this purpose</i>	7 - 8	
<i>Generally usable, but not the best choice</i>	5 - 6	
<i>Generally not usable for this purpose</i>	3 - 4	
<i>Wrong choice</i>	1 - 2	

Check material compatibility with every process change!

Industrial chemical product.

Read MSDS before use.

Disclaimer:

This information is intended as advice to the best of our knowledge. The provided data is based on our own measurements, they do not provide any guaranteed properties nor are these delivery specifications. Due to the versatility of materials, applications and taking in consideration the industrial property rights of third parties, Balver Zinn GmbH cannot take any liability.

CLASSIFICATION

DIN-EN-ISO-9454-1: 2016	1122
IPC-J-STD-004-A: 2004	ROL0
IPC-J-STD-005: 1995 (Powder)	T4
Particle size	[µm] 20-38

PROPERTIES

Flux code	JEAN-151	
Alloy Code	SnPb36Ag2	
Alloy composition	Sn62Pb36Ag2	
Liquidus	[°C]	179
Solidus	[°C]	179
Recommended peak temp.	[°C]	205-225
Acid number	[mg KOH/g]	123
Flux	[% w/w]	9.9
Residues	Colorless	
Tackiness Malcom TK1	IPC-TM-650 2.4.44	[gf] @ 0h 40

TEST REPORTS

IPC/ANSI-J-STD-005	Compliant	
Certificate of Compliance	Website	
Declaration of Conformity 2011/65/EU (RoHS)	No	
Application Note	EN/DE	
Copper Mirror	IPC-TM-650 2.3.32	Pass
Halides	IPC-TM-650 2.3.33	[Silver Chromate] Pass
Halide	IPC-TM-650 2.3.35.1	[Fluoride by Spot] Pass
Copper Corrosion	IPC-TM-650 2.6.15	Pass
SIR	IPC-TM-650 2.6.3.3	Pass
ECM	IPC-TM-650 2.6.14.1	Pass

PACKAGING AND STORAGE

Packaging jar	PP [g]	500
Packaging cartridge	HDPE [g]	650
Packaging cartridge	HDPE [g]	1300
Packaging Cassette Pro-Flow	[g]	850
Minimum shelf-life in months	4-10°C	6
Minimum shelf-life in months	< 25 °C	6