Product data sheet

BALVER ZINN®

SAC3-HF3+

Pav: 15 1

 Date
 2025.09.02

 Language
 English

 SDS
 950608





SUMMARY

Pb-free - Halide-free - No-Clean solder paste - Fine Pitch

PASTE	SAC3-HF3+	
PROCESS		
No-Clean process		9
Post-solder cleaning		6

INDUSTRY APPLICATION		
Standard electronics	8	
Industrial electronics	9	
Hi-Rel electronics (automotive)	8	

PROCESS CAPABILITY		
Squeegee	9	
ProFlow	TBD	
Pb-free Profile Air, short	8	
Pb-free Profile Air, long	8	
Pb-free process N2	9	
Vapor phase process	8	
Shiny joint appearance	8	
Cosmetic cleanliness	8	
ICCT compatible	9	
Conformal coating	6	

Legend		
Especially made for this purpose	9 - 10	
Generally qualified for this purpose		
Generally usable, but not the best choice		
Generally not usable for this purpose		
Wrong choice	1 - 2	

Check material compatibility with every process change!

Industrial chemical product.

Read MSDS before use.

4-10 °C

CLASSIFICATION			
DIN-EN-29454-1: 1994	1.2.3.C		
IPC-J-STD-004-A: 2004	REL0		
IPC-J-STD-005: 1995 (Powder)	T4		
Particle size [µm]	20-38		

PROPERTIES			
Flux code		F3+	
Alloy Code		SAC3	
Alloy composition		Sn96.5Ag3Cu0.5	
Liquidus		[°C]	219
Solidus		[°C]	217
Recommended peak temp.		[°C]	232-250
Acid number		[mg KOH/g]	124.3
Flux		[% w/w]	12.1
Residues			Colorless
Tackiness Malcom TK1	JIS-Z-3284	[gf] @ 0h	110

TEST REPORTS			
IPC/ANSI-J-STD-005		Compliant	
Certificate of Compliance			Website
Declaration of Conformity 2011/65/EU (RoHS)			Available
Application Note		EN/DE	
Copper Mirror	IPC-TM-650 2.3.32		Pass
Halides	IPC-TM-650 2.3.33	[Silver Chromate]	Pass
Halide	IPC-TM-650 2.3.35.1	[Fluoride by Spot]	Pass
Copper Corrosion	IPC-TM-650 2.6.15		Pass
SIR	IPC-TM-650 2.6.3.3		Pass
ECM	IPC-TM-650 2.6.14.1		Pass

PACKAGING AND STORAGE		
Packaging jar	PP [g]	500
Packaging cartridge	HDPE [g]	650
Packaging cartridge	HDPE [g]	1300
Packaging Cassette Pro-Flow	[9]	800
Minimum shelf-life in months	4-10 °C	-
Minimum shelf-life in months	4-10 °C	6

Disclaimer

This information is intended as advice to the best of our knowledge. The provided data is based on our own measurements, they do not provide any guaranteed properties nor are these delivery specifications. Due to the versatility of materials, applications and taking in consideration the industrial property rights of third parties, Balver Zinn Josef Jost GmbH & Co. KG cannot take any liability.