

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Leaded Solder Wire Alloy based on Tin-Lead or Lead-Tin with Resin based Flux

Revision date: 03.07.2018

Product code: 950203

Page 1 of 11

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Leaded Solder Wire Alloy based on Tin-Lead or Lead-Tin with Resin based Flux

**Further trade names**possible alloys: Sn60Pb40; Sn63Pb37; Sn64Pb36; Sn60Pb38Cu2; Sn60Pb38Ag2; Sn60Pb36Ag4;  
Sn62Pb36Ag2; Pb60Sn40; Pb90Sn10; Pb62Sn27Ag3; Pb93Sn5Ag2; Pb95,5Sn3Ag1,5

2220; 3135; B2012; 26Q; 32Q; B211; Cobar 393

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Solder wire

**Uses advised against**

Any non-intended use.

**1.3. Details of the supplier of the safety data sheet**

Company name:	Balver Zinn Josef Jost GmbH & Co. KG	
Street:	Blintroper Weg 11	
Place:	D-58802 Balve	
Telephone:	+49 2375 915-0	Telefax: +49 2375 915-1700
Responsible Department:	sds@balverzinn.com	

**1.4. Emergency telephone number:** Chemtrec: +44(0) 870-8200418**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Reproductive toxicity: Repr. 1A

Reproductive toxicity: Lact.

Specific target organ toxicity - repeated exposure: STOT RE 1

Hazard Statements:

May damage fertility. May damage the unborn child.

May cause harm to breast-fed children.

Causes damage to organs through prolonged or repeated exposure.

**2.2. Label elements****Additional advice on labelling**

Labelling according to Regulation (EC) No. 1272/2008 [CLP]: none

For this product, a hazard label is not required according to section 1.3.4 of the CLP regulation.

**2.3. Other hazards**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Chemical characterization**

Solder wire

**Hazardous components**

CAS No	Chemical name	Quantity
--------	---------------	----------

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Leaded Solder Wire Alloy based on Tin-Lead or Lead-Tin with Resin based Flux

Revision date: 03.07.2018

Product code: 950203

Page 2 of 11

	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
7439-92-1	lead massive [particle diameter >= 1 mm]			95 - <= 100 %
	231-100-4	082-014-00-7	01-2119513221-59	
	Repr. 1A, Lact., STOT RE 1; H360FD H362 H372			
7440-31-5	tin			2 - 65 %
	231-141-8		01-2119486474-28	
7440-22-4	silver			0,2 - 5 %
	231-131-3		01-2119555669-21	
7440-50-8	copper			0 - 5 %
	231-159-6			
65997-06-0	Rosin, hydrogenated			1 - < 5 %
	266-041-3			

Full text of H and EUH statements: see section 16.

**Further Information**

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: lead massive [particle diameter >= 1 mm] CAS n°: 7439-92-1

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

**After inhalation**

In case of accident by inhalation: remove casualty to fresh air and keep at rest. When in doubt or if symptoms are observed, get medical advice.

**After contact with skin**

No special measures are necessary.

The melted product can cause severe burns. After contact with molten product, cool skin area rapidly with cold water. Burns caused by molten material must be treated clinically.

**After contact with eyes**

No special measures are necessary.

**After ingestion**

No special measures are necessary.

**4.2. Most important symptoms and effects, both acute and delayed**

No information available.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Sand

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Leaded Solder Wire Alloy based on Tin-Lead or Lead-Tin with Resin based Flux**

Revision date: 03.07.2018

Product code: 950203

Page 3 of 11

Extinguishing powder

D -powder

**Unsuitable extinguishing media**

Extinguishing media which must not be used for safety reasons:

Water

High power water jet

Water spray jet

**5.2. Special hazards arising from the substance or mixture**Can be released in case of fire: Gas/vapours, irritant. Carbon monoxide Carbon dioxide (CO<sub>2</sub>). Nitrogen oxides (NO<sub>x</sub>). Metal oxide smoke, toxic**5.3. Advice for firefighters**

In case of fire and/or explosion do not breathe fumes.

In case of fire: Wear self-contained breathing apparatus.

**Additional information**

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

See protective measures under point 7 and 8.

**6.2. Environmental precautions**

No special measures are necessary.

**6.3. Methods and material for containment and cleaning up**

Take up mechanically, placing in appropriate containers for disposal.

Clean contaminated objects and areas thoroughly observing environmental regulations.

**6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means. Process within closed systems.

Do not breathe smoke. Do not breathe dust.

**Advice on protection against fire and explosion**

No special fire protection measures are necessary.

**Further information on handling**

General protection and hygiene measures: See section 8.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

No special measures are necessary.

**Advice on storage compatibility**

Do not store together with: Explosives. Oxidizing solids. Oxidizing liquids. Radioactive substances. Infectious substances.

**7.3. Specific end use(s)**

refer to chapter 1.

**SECTION 8: Exposure controls/personal protection**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Leaded Solder Wire Alloy based on Tin-Lead or Lead-Tin with Resin based Flux**

Revision date: 03.07.2018

Product code: 950203

Page 4 of 11

**8.1. Control parameters**

**Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
7440-50-8	Copper, dusts and mists (as Cu)	-	1		TWA (8 h)	WEL
		-	2		STEL (15 min)	WEL
7440-50-8	Copper, fume	-	0.2		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL
-	Lead other than lead alkyls	-	0.15		TWA (8 h)	CLAW
		-	-		STEL (15 min)	CLAW
7440-22-4	Silver, metallic	-	0.1		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL
-	Tin compounds, inorganic, except SnH <sub>4</sub> , (as Sn)	-	2		TWA (8 h)	WEL
		-	4		STEL (15 min)	WEL

**Biological Monitoring Guidance Values (EH40)**

CAS No	Substance	Parameter	Value	Test material	Sampling time
7439-92-1	Lead (woman of reproductive capacity)	lead	20 µg/dl	blood	Random

**DNEL/DMEL values**

CAS No	Substance	DNEL type	Exposure route	Effect	Value
7440-31-5	tin	Consumer DNEL, long-term	inhalation	systemic	3,476 mg/m <sup>3</sup>
		Consumer DNEL, acute	inhalation	systemic	3,476 mg/m <sup>3</sup>
		Worker DNEL, long-term	inhalation	systemic	11,75 mg/m <sup>3</sup>
		Worker DNEL, acute	inhalation	systemic	11,75 mg/m <sup>3</sup>
		Consumer DNEL, long-term	dermal	systemic	80 mg/kg bw/day
		Worker DNEL, acute	dermal	systemic	133,3 mg/kg bw/day
		Consumer DNEL, acute	dermal	systemic	80 mg/kg bw/day
		Worker DNEL, long-term	dermal	systemic	133,3 mg/kg bw/day
		Consumer DNEL, acute	oral	systemic	80 mg/kg bw/day
		Consumer DNEL, long-term	oral	systemic	80 mg/kg bw/day
7440-22-4	silver	Consumer DNEL, long-term	oral	systemic	1,2 mg/kg bw/day
		Worker DNEL, long-term	inhalation	systemic	0,1 mg/m <sup>3</sup>
		Consumer DNEL, long-term	inhalation	systemic	0,04 mg/m <sup>3</sup>
7440-50-8	copper	Worker DNEL, acute	dermal	systemic	273 mg/kg bw/day
		Consumer DNEL, acute	dermal	systemic	273 mg/kg bw/day

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Leaded Solder Wire Alloy based on Tin-Lead or Lead-Tin with Resin based Flux**

Revision date: 03.07.2018

Product code: 950203

Page 5 of 11

Consumer DNEL, acute	inhalation	systemic	20 mg/m³
Worker DNEL, long-term	inhalation	local	1 mg/m³
Consumer DNEL, long-term	dermal	systemic	137 mg/kg bw/day
Worker DNEL, long-term	dermal	systemic	137 mg/kg bw/day
Worker DNEL, acute	inhalation	systemic	20 mg/m³
Consumer DNEL, long-term	inhalation	local	1 mg/m³

**PNEC values**

CAS No	Substance		Value
Environmental compartment			
7440-22-4	silver		
Soil			1,41 mg/kg
Freshwater			0,00004 mg/l
Marine sediment			438,13 mg/kg
Freshwater sediment			438,13 mg/kg
Marine water			0,00086 mg/l
Micro-organisms in sewage treatment plants (STP)			0,025 mg/l
7440-50-8	copper		
Freshwater			0,0078 mg/l
Marine water			0,0052 mg/l
Freshwater sediment			87 mg/kg
Marine sediment			678 mg/kg
Micro-organisms in sewage treatment plants (STP)			0,23 mg/l
Soil			65 mg/kg

**8.2. Exposure controls**



**Appropriate engineering controls**

Provide adequate ventilation as well as local exhaust at critical locations.  
Process within closed systems.

**Protective and hygiene measures**

Keep away from food, drink and animal feedingstuffs. Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff. Use protective skin cream before handling the product.

**Eye/face protection**

Wear eye/face protection.

**Hand protection**

Wear suitable gloves.

for coarse soldering works: heat insulating.

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

In the case of wanting to use the gloves again, clean them before taking off and air them well. Before using check leak tightness / impermeability.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Leaded Solder Wire Alloy based on Tin-Lead or Lead-Tin with Resin based Flux**

Revision date: 03.07.2018

Product code: 950203

Page 6 of 11

**Skin protection**

Protective clothing (heat-resistant)

**Respiratory protection**

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

Insufficient ventilation.

exceeding exposure limit values

Suitable respiratory protective equipment: Particle filter device (DIN EN 143) Type: P3

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

**Environmental exposure controls**

No special environmental measures are necessary.

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Physical state:	solid	
Colour:	metallic, silver	
Odour:	odourless	
pH-Value:		not applicable

**Changes in the physical state**

Melting point:		not determined
Initial boiling point and boiling range:		not determined
Sublimation point:		not determined
Softening point:		not determined
Flash point:		not determined

**Flammability**

Solid:		not determined
--------	--	----------------

**Explosive properties**

none

Lower explosion limits:		not determined
Upper explosion limits:		not determined
Ignition temperature:		not determined

**Auto-ignition temperature**

Solid:		not determined
--------	--	----------------

Decomposition temperature:		not determined
----------------------------	--	----------------

**Oxidizing properties**

none

Vapour pressure:		not determined
------------------	--	----------------

Density:		not determined
----------	--	----------------

Bulk density:		not determined
---------------	--	----------------

Water solubility:		insoluble
-------------------	--	-----------

**Solubility in other solvents**

insoluble

Viscosity / dynamic:		not determined
----------------------	--	----------------

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Leaded Solder Wire Alloy based on Tin-Lead or Lead-Tin with Resin based Flux**

Revision date: 03.07.2018

Product code: 950203

Page 7 of 11

Viscosity / kinematic: not determined

**9.2. Other information**

Solid content: not determined

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

No information available.

**10.2. Chemical stability**

The product is chemically stable under recommended conditions of storage, use and temperature.

**10.3. Possibility of hazardous reactions**

No known hazardous reactions.

**10.4. Conditions to avoid**

No information available.

**10.5. Incompatible materials**

No information available.

**10.6. Hazardous decomposition products**

Can be released in case of fire: Metal oxide smoke, toxic

**SECTION 11: Toxicological information**

**11.1. Information on toxicological effects**

**Toxicokinetics, metabolism and distribution**

No information available.

**Acute toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
7439-92-1	lead massive [particle diameter >= 1 mm]				
	oral	LD50 > 2000 mg/kg	Rat	Study report (2003)	OECD Guideline 423
	dermal	LD50 > 2000 mg/kg	Rat	Study report (2003)	OECD Guideline 402
7440-31-5	tin				
	oral	LD50 >2000 mg/kg	Rat	ECHA Dossier	
	dermal	LD50 >2000 mg/kg	Rat	ECHA Dossier	
	inhalation (4 h) aerosol	LC50 (>4,75) mg/l	Rat	ECHA Dossier	
7440-22-4	silver				
	oral	LD50 >2000 mg/kg	Rat	ECHA Dossier	
	dermal	LD50 >2000 mg/kg	Rat	ECHA Dossier	
	inhalation (4 h) aerosol	LC50 >5,16 mg/l	Rat	ECHA Dossier	
7440-50-8	copper				

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Leaded Solder Wire Alloy based on Tin-Lead or Lead-Tin with Resin based Flux

Revision date: 03.07.2018

Product code: 950203

Page 8 of 11

	inhalation (4 h) aerosol	LC50 mg/l	>5,11	Rat	ECHA Dossier	
--	--------------------------	--------------	-------	-----	--------------	--

**Irritation and corrosivity**

Based on available data, the classification criteria are not met.

Skin corrosion/irritation: Not an irritant.

Serious eye damage/eye irritation: Not an irritant.

**Sensitising effects**

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation: not sensitising.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Specific effects in experiment on an animal**

No data available

**SECTION 12: Ecological information****12.1. Toxicity**

No data available

**12.2. Persistence and degradability**

No data available

**12.3. Bioaccumulative potential**

No indication of bioaccumulation potential.

**BCF**

CAS No	Chemical name	BCF	Species	Source
7439-92-1	lead massive [particle diameter >= 1 mm]	40000	Asellus meridianus	Freshwater Biology 7

**12.4. Mobility in soil**

No data available

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Other adverse effects**

No data available

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Advice on disposal**

Dispose of waste according to applicable legislation. Consult the local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. According to EAKV, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Control report for waste code/ waste marking according to EAKV:

**Waste disposal number of waste from residues/unused products**

160303 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; off-specification batches and unused products; inorganic wastes containing hazardous substances; hazardous waste



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Leaded Solder Wire Alloy based on Tin-Lead or Lead-Tin with Resin based Flux

Revision date: 03.07.2018

Product code: 950203

Page 9 of 11

**Waste disposal number of used product**

160303 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; off-specification batches and unused products; inorganic wastes containing hazardous substances; hazardous waste

**Waste disposal number of contaminated packaging**

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

**Contaminated packaging**

Handle contaminated packages in the same way as the substance itself.

**SECTION 14: Transport information****Land transport (ADR/RID)**

**14.1. UN number:** Not restricted  
**14.2. UN proper shipping name:** Not restricted  
**14.3. Transport hazard class(es):** Not restricted  
**14.4. Packing group:** Not restricted

**Inland waterways transport (ADN)**

**14.1. UN number:** Not restricted  
**14.2. UN proper shipping name:** Not restricted  
**14.3. Transport hazard class(es):** Not restricted  
**14.4. Packing group:** Not restricted

**Marine transport (IMDG)**

**14.1. UN number:** Not restricted  
**14.2. UN proper shipping name:** Not restricted  
**14.3. Transport hazard class(es):** Not restricted  
**14.4. Packing group:** Not restricted

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number:** Not restricted  
**14.2. UN proper shipping name:** Not restricted  
**14.3. Transport hazard class(es):** Not restricted  
**14.4. Packing group:** Not restricted

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: no

**14.6. Special precautions for user**

Not restricted

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

Not restricted

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 63: lead massive [particle diameter  $\geq 1$  mm]

Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III)  
(SEVESO III):

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Leaded Solder Wire Alloy based on Tin-Lead or Lead-Tin with Resin based Flux

Revision date: 03.07.2018

Product code: 950203

Page 10 of 11

**Additional information**

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].  
REACH 1907/2006 Appendix XVII, No: 63

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of child-bearing age.

Water contaminating class (D): 1 - slightly water contaminating

**Additional information**

Observe technical data sheet.

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information****Changes**

Rev. 1.00; 22.05.2015, Initial release  
Rev.1.1; 16.11.2016, Indication of changes - chapter: 1, 2, 3, 16.  
Rev. 2,0 ; 13.04.2018, Changes in chapter: 2,3, 15.  
Rev. 2,1 ; 03.07.2018, Changes in chapter: 3.

**Abbreviations and acronyms**

ADR: Accord européen sur le transport des marchandises dangereuses par Route  
CAS Chemical Abstracts Service  
DNEL: Derived No Effect Level  
IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER

IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)  
ICAO: International Civil Aviation Organization  
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)  
GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)  
LOAEL: Lowest observed adverse effect level  
LOAEC: Lowest observed adverse effect concentration  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
NOAEL: No observed adverse effect level  
NOAEC: No observed adverse effect level  
NTP: National Toxicology Program  
N/A: not applicable  
OSHA: Occupational Safety and Health Administration  
PNEC: predicted no effect concentration  
PBT: Persistent bioaccumulative toxic  
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail )  
SARA: Superfund Amendments and Reauthorization Act  
SVHC: substance of very high concern  
TRGS Technische Regeln fuerGefahrstoffe  
TSCA: Toxic Substances Control Act  
VOC: Volatile Organic Compounds

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

**Leaded Solder Wire Alloy based on Tin-Lead or Lead-Tin with Resin based Flux**

Revision date: 03.07.2018

Product code: 950203

Page 11 of 11

VwVwS: Verwaltungsvorschrift wassergefährdender Stoffe

WGK: Wassergefährdungsklasse

**Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]**

Classification	Classification procedure
Repr. 1A; H360FD	Calculation method
Lact.; H362	Calculation method
STOT RE 1; H372	Calculation method

**Relevant H and EUH statements (number and full text)**

H360FD	May damage fertility. May damage the unborn child.
H362	May cause harm to breast-fed children.
H372	Causes damage to organs through prolonged or repeated exposure.

**Further Information**

Classification according EC regulation 1272/2008 (CLP): - Classification procedure:

Health hazards: Calculation method.

Environmental hazards: Calculation method.

Physical hazards: On basis of test data. and / or calculated and / or estimated.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*